

SERIES ORBIT | LED HIGH PERFORMANCE RECESSED DOWNLIGHT

PRESSURE-FIT CLIP SYSTEM

Pressure-fit spring clips for ease of install.

HIGH PERFORMANCE LED

Integrated COB technology offers low-energy, long lasting performance with outstanding light outputs of 850 lumens.


ANTI-GLARE LIGHTING

Regressed led light source offers anti-glare lighting.


FOCUSED SPOT

A 36° focused spot with a 360° rotation will answer multiple lighting applications.


AVAILABLE IN






SATIN CHROME



BLACK



WHITE



INTEGRATED DRIVER

Aluminum junction box with integrated dimming driver & Quick Connect wire connectors for easy connection.



DIMMABLE

IC

RATED



UL



ENERGY STAR

* Optional: 120-277V Driver (0-10 V dimming)

NOMINAL SIZE	MODEL	SHAPE	LIGHT OUTPUT*	WATTAGE VOLTAGE	LUMINAIRE DIMENSIONS	JUNCTION BOX DIMENSIONS
3"	OB300	ROUND	850 LM	10 W / 120 V	3.75" x 2.4"	5.3" x 2.6" x 2.0"
	OB330	SQUARE				
4"	OB400	ROUND				
	OB430	SQUARE				
CRI	HOLE SIZE	GIMBAL ANGLE	COLOR TEMPERATURE	LIFETIME	LIMITED WARRANTY	
80+	3.25"	27°	3000K, 4000K	50,000 HOURS	5 YEARS	