



WHITE

BLACK

SATIN  
CHROME



## OB-LED-400

### 4" HIGH PERFORMANCE ORBIT SERIES - 10W

#### Product codes

OB400-0510-3K-WH : WHITE - 3K

OB400-0510-3K-BK : BLACK - 3K

OB400-0510-3K-SC : SATIN CHROME - 3K

OB400-0510-4K-WH : WHITE - 4K

OB400-0510-4K-BK : BLACK - 4K

OB400-0510-4K-SC : SATIN CHROME - 4K

OB400-0510-3K-WH-CRI90 : WHITE - 3K (CRI 90)

OB400-0510-4K-WH-CRI90 : WHITE - 4K (CRI 90)

High performance LED recessed downlight with a pressure-fit spring clips application for an easy install. Integrated COB technology offers low-energy, long lasting performance with outstanding light outputs of 850 LUMENS. Available in a CRI 80 or CRI 90 version.

Suitable for residential applications, this regressed LED light source offers an anti-glare lighting. A 36 degree focused beam angle with a 360 degree rotation will answer many lighting applications.

The body is constructed of die cast aluminum, with junction box manufactured in aluminum extrusion. For easy and quick installation, the unit comes with pressure-fit spring clips and quick connect wire connectors. Dimmable driver included.

#### Données techniques

|                       |                       |
|-----------------------|-----------------------|
| Cutting hole          | 3.75" (95.3 mm)       |
| Beam Angle            | 36° ± 1/2             |
| Adjustment angle      | 27° ± 1/2             |
| Head Rotation         | 360° ± 1/2            |
| Color Temperature     | 3000K / 4000K         |
| Mounting Plate        | MP300/AMP300/MPHB-350 |
| CRI                   | >80 or 90             |
| Dimmable              | Y                     |
| Bulb Life             | 50,000hrs             |
| Light Output - Lumen  | 850LM - CRI 80        |
| Operating Temperature | -20°C + 40°C          |
| Voltage               | 120VV                 |
| Watt                  | 10W                   |
| Warranty (Years)      | 5                     |

