

TL350-24V
PINNACLE SERIES
24V LED TAPE LIGHT
SPECIFICATION GRADE
FIELD CUTTABLE

Can be cut every 4"

ACTUAL SIZE SHOWN

10mm tape


DESCRIPTION

NDR Pinnacle 350 Series LED Tape Light has market leading and near perfect color rendering with CRI>94. We choose top quality LEDs with 3-Step MacAdam binning for uniformity in both color and intensity.

SPECIFICATIONS

Model	TL350-24V
Certificates	cULus
Input voltage	24V
Watts/FT	2.9W/FT
Watts/M	9.6W/m
CRI	94+
Dimmable	Yes
IP Rating	IP20
LEDs/FT	24 LEDs/FT
Dimensions	0.4 x 196 x 0.07" / 10 x 5000 x 1.8mm
Cutttable section	Every 4" / 10cm
Beam angle	120°
Lifetime	50,000H
Mounting	3M self-adhesive tape (non-porous)
Operating temperature	-20C to 45C / -4F to -113F
Max run	8m / 26.2ft
Limited warranty	5 years

FEATURES

- Full range dimmability
- 30Z copper
- 3-Step MacAdam LED binning
- Cuttable every 4"
- Maximum run is 26FT (8m)
- 3M™ double sided tape
- Suitable for use in closet spaces
- IP20 - dry location










MODEL	WATTS / FT	LM / FT	WATTS / M	LM / M	CRI	REEL SIZE	IP RATING	LIFETIME	LIMITED WARRANTY
TL350-24V-27K	2.9	316	9.6	1036	94+	16.4FT (5M)	IP20	50,000 HOURS	5 YEARS
TL350-24V-3K		322		1056					
TL350-24V-4K		339		1113					
TL350-24V-3K-30		322		1056		98.4FT (30M)			

* TL350-24V tape is fully dimmable when powered by NDR LED Class 2 drivers (TLD24V-30W, TLD24V-60W or TLD24V-96W).

RATINGS




ACCESSORIES

	<p>TL-STT-2-10 2-Pin screw connector, tape to tape connector (8-10mm)</p>		<p>TL-CTT-2-10 2-Pin tape to tape connector (10mm)</p>
	<p>TL-STW8-2-10 2-Pin screw connector, tape to 8" wire lead (8-10mm)</p>		<p>TL-CTW6-2-10 2-Pin tape to 6" wire lead connector (10mm)</p>
	<p>TL-SJOIN8-2-10 2-Pin screw connector, tape to tape with 8" wire lead (8-10mm)</p>		<p>TL-CJOIN6-2-10 2-Pin tape to tape joiner with 6" wire lead (10mm)</p>
	<p>TL-SLTT-2-10 2-Pin screw connector, tape to tape L-corner (8-10mm)</p>		

TL350-24V
PINNACLE SERIES
24V LED TAPE LIGHT
SPECIFICATION GRADE
SPECIAL ORDER ITEMS

MODEL	WATTS / FT	LM / FT	WATTS / M	LM / M	CRI	REEL SIZE	IP RATING	LIFETIME	LIMITED WARRANTY
TL350-24V-18K	2.9	293	9.6	960	94+	16.4FT (5M)	IP20	50,000 HOURS	5 YEARS
TL350-24V-21K		307		1008					
TL350-24V-23K		322		1056					
TL350-24V-35K									
TL350-24V-5K									
TL350-24V-65K		325		1065					

* Special order MOQs: 5x 5m reels or 1x 30m reels

LED DRIVERS

TLD24V-30W

30W Class 2 LED Driver
 120-277V Input, 24V Output, TRIAC, ELV, MLV
 Forward & reverse phase, PWM output
 1/2" knockout size
 Wet location rated
 Dimensions: 6.5" x 3.7" x 1.6" / 165mm x 94.5mm x 40mm


TLD24V-60W

60W Class 2 LED driver
 100-277V input, 24V output, TRIAC, ELV, MLV
 Forward & reverse phase, PWM output
 1/2" Knockout size
 Wet location rated
 Dimensions: 7.4" x 3.7" x 1.6" / 188mm x 94.5mm x 40mm


TLD24V-96W

96W Class 2 LED driver
 100-277V input, 24V output, TRIAC, ELV, MLV,
 Forward & reverse phase, PWM output
 1/2" Knockout size
 Wet location rated
 Dimensions: 8.7" x 3.7" x 1.6" / 220mm x 94.5mm x 40mm