

PINNACLE SERIES

ACCESSORIES & DRIVERS
MATRIX SHEETS



PINNACLE SERIES

ACCESSORIES

MATRIX SHEET

		TL350	TL600	TL170	TL360	TL250	TL200
	Watts/foot	2.9 W/ft.	5.1 W/ft.	1.9 W/ft.	4.6 W/ft.	2.9 W/ft.	3.7 W/ft.
	Lumens/foot	322 lm/ft.	563 lm/ft.	179 lm/ft.	388 lm/ft.	236 lm/ft.	198 lm/ft.
	Reel size	16.4ft. / 5m	16.4ft. / 5m	49.2ft. / 15m	16.4ft. / 5m	32.8ft. / 10m	16.4ft. / 5m
	Max run	26.2ft. / 8m (76W)	16.4ft. / 5m (84W)	49.2ft. / 15m (94W)	16.4ft. / 5m (76W)	32.8ft. / 10m (96W)	25.9ft. / 7.8m (95W)
	Accessories						
2-pin screw connectors	TL-DUAL-2-10 	•	•	•	•	•	
	TL-STB-2-10 	•	•	•	•	•	
	TL-STT-2-10 	•	•	•	•	•	
	TL-STW8-2-10 	•	•	•	•	•	
	TL-SJOIN8-2-10 	•	•	•	•	•	
	TL-SLTT-2-10 	•	•	•	•	•	
	TL-EXT6FT-2-10 	•	•	•	•	•	
6-pin snap connectors	TL-CTT-6-12 						•
	TL-CTW6-6-12 						•
	TL-CJOIN6-6-12 						•
	TL-EXT-20FT-6-12 						•
Controllers & remotes	TL-WIFI-CTLR 						•
	TL-RGBCCT-RMT 						•

PINNACLE SERIES

ACCESSORIES

MATRIX SHEET

		TL150	TL260	TL290	TL400
	Watts/foot	4.6 W/ft.	3 W/ft.	2.9 W/ft.	4.5 W/ft.
	Lumens/foot	138 lm/ft.	272 lm/ft.	290 lm/ft.	414 lm/ft.
	Reel size	16.4ft. / 5m	16.4ft. / 5m	26.2ft. / 8m	100ft. / 30.5m
	Max run	16.4ft. / 5m (75W)	16.4ft. / 5m (49W)	26.2ft. / 8m (76W)	100ft. / 30.5m (450W)
	Accessories				
5-pin RGB Neonflex connectors	TL-EC24V-1515 	•			
	TL-WL6-1515 	•			
	TL-JOIN6-1515 	•			
	TL-CLIP-1515 	•			
Controllers & Remotes	TL-WIFI-CTLR 	•			
	TL-RGBW-RMT 	•			
TL260 2-pin wet location COB67 connectors	TL-EC-COB67 		•		
	TL-WL6FT-COB67 		•		
	TL-JOIN12-COB67 		•		
	TL-CLIP-COB67 		•		
TL290 2-pin wet location connectors	TL-290-EC 			•	
	TL-290-WL6FT 			•	
	TL-290-JOIN12 			•	
	TL-290-CLIP 			•	
120V accessories	TL-CLIP120V 				•
	TL-EC120V 				•

PINNACLE SERIES

24V DRIVERS

MATRIX SHEET

		TL350	TL600	TL170	TL360	TL250	TL200	TL150	TL260	TL290	PL24V-CCT
	Watts/foot	2.9W/ft.	5.1W/ft.	1.9W/ft.	4.6W/ft.	2.9W/ft.	3.7W/ft.	4.6W/ft.	3W/ft.	2.9W/ft.	3.5W
	Lumens/foot	322lm/ft.	563lm/ft.	179lm/ft.	388lm/ft.	236lm/ft.	198lm/ft.	138lm/ft.	272lm/ft.	290lm/ft.	120lm
	Reel size	16.4ft./5m	16.4ft./5m	49.2ft./15m	16.4ft./5m	32.8ft./10m	16.4ft./5m	16.4ft./5m	16.4ft./5m	26.2ft./8m	
	Max run	26.2ft./8m (76W)	16.4ft./5m (84W)	49.2ft./15m (94W)	16.4ft./5m (75W)	32.8ft./10m (96W)	25.9ft./7.8m (95W)	16.4ft./5m (75W)	16.4ft./5m (49W)	26.2ft./8m (76W)	
	Drivers										
Drivers Maximum lengths	TLD24V-25W 	8.6ft 2.6m	4.9ft 1.5m	13.1ft 3.9m	5.4ft 2.6m	8.6ft 2.6m	6.7ft 2m	5.4ft 1.6m	8ft 2.5m	8.6ft 2.6m	7 puck lights
	TLD24V-30W 	10ft 3m	5.8ft 1.7m	15.7ft 4.7m	6.5ft 2m	10ft 3m	8.1ft 2.5m	6.5ft 2m	10ft 3m	10ft 3m	8 puck lights
	TLD24V-60W 	20ft 6.1m	11.7ft 3.5m	31.5ft 9.6m	13ft 4m	20ft 6.1m	16.4ft 5m	13ft 3.9m	20ft 6.1m	20ft 6.1m	17 puck lights
	TLD24V-96W 	33ft 10m	18.8ft 5.7m	50.5ft 15.3m	20ft 6m	33ft 10m	25.9ft 7.8m	20ft 6m	32ft 9.7m	33ft 10m	
	TLD24V-192W 	66.3ft 20.1m	37.6ft 11.5m	101ft 30.7m	41.7ft 12.7m	66.2ft 20.1m	51.9ft 15.8m	41.7ft 12.7m	64ft 19.5m	66.2ft 20.1m	
	TLD24V-288W 	99.3ft 30.3m	56.5ft 17.2m	151.5ft 46.1m	62.6ft 19m	99.3ft 30.3m	77.8ft 23.7m	62.6ft 19m	96ft 29.2m	99.3ft 30.3m	
	TLD24V-MINI-60W 	20ft 6.1m	11.7ft 3.5m	31.5ft 9.6m	13ft 4m	20ft 6.1m	16.4ft 5m	13ft 3.9m	20ft 6.1m	20ft 6.1m	17 puck lights
	TLD24V-MINI-96W 	33ft 10m	18.8ft 5.7m	50.5ft 15.3m	20ft 6m	33ft 10m	25.9ft 7.8m	20ft 6m	32ft 9.7m	33ft 10m	
	TLDDIM24V-60W 	20ft 6.1m	11.7ft 3.5m	31.5ft 9.6m	13ft 4m	20ft 6.1m	16.4ft 5m	13ft 3.9m	20ft 6.1m	20ft 6.1m	17 puck lights
	TLDDIM24V-96W 	33ft 10m	18.8ft 5.7m	50.5ft 15.3m	20ft 6m	33ft 10m	25.9ft 7.8m	20ft 6m	32ft 9.7m	33ft 10m	
	TLDDIM24V-160W 	55.1ft 16.7m	31.3ft 9.5m	84.2ft 25.6m	34.7ft 10.5m	55.1ft 16.7m	43.2ft 13.1m	34.7ft 10.5m	53.3ft 16.2m	55.1ft 16.7m	